

# CABLEMATE

## PLASTIC CABLE GLAND

Supplied complete with locknut




**IP68 Protection at 5 bar (72 psi)**

50 metres submersible

### FEATURES

- The range covers cables from outside diameters of 2.5 mm to 54 mm
- Integral claw type cable grip
- Nut will not thread bounce
- Low profile above mounting surface

ALSO AVAILABLE WITH WAVE SEAL™ IP68 SURFACE MOUNTING SEALING WASHER

Cat No.	Thread size	Thread Length	 mm	Cable Range OD	Pack size
GX12	M12 x 1.5	10	15	2.5 - 6	50
GX16	M16 x 1.5	15	22	4.5 - 10.2	50
GX20	M20 x 1.5	15	27	7.5 - 13.2	50
GX25	M25 x 1.5	15	32	13 - 18	25
GX32	M32 x 1.5	15	42	17.5 - 25	20
GX40	M40 x 1.5	15	51	24.5 - 31.5	5
GX50	M50 x 1.5	15	65	31- 43	2
GX63	M63 x 1.5	18	80	43 - 54	2

### TECHNICAL DATA

**Material:** Nylon

**Colour:** Black or Grey

**Working temp:** -40°C to 100°C  
Short term 130°C

**Chemical resistance:**

Excellent resistance to oils, petrol, alcohols, seawater, caustic soda, weak acids, alkalis bases and salts.

Additional technical information available on request

Dimensions and specifications may be changed without notice.



A product designed, manufactured and distributed by

**McCABE INDUSTRIES LTD**

Plastics Engineers and Injection Moulders

9-11 Nicolaus Street, Upper Hutt 5018, New Zealand  
Phone: 04-528 9619 Fax: 04-527 9051